



NF-A4x20 PWM

40x40x20mm. 4-pin PWM. 5000rpm.



NF-A4X20 PWM

SPECIFICATIONS

VIDEOS

REVIEWS

SERVICE

ACCESSORIES

 BUY



FAN Specification

Size	40x40x20 mm
Mounting hole spacing	32x32 mm
<u>Connector & pin-configuration</u>	4-pin PWM
Cable length	20cm + 30cm NA-EC1 extension cable
Bearing	SSO2
Blade geometry	A-Series with Flow Acceleration Channels
Frame technology	AAO (Advanced Acoustic Optimisation)
Rotational speed (+/- 10%)	5000 RPM
Rotational speed with L.N.A. (+/- 10%)	4400 RPM
Min. rotational speed @ 20% PWM (+/-20%)	1200 RPM
<u>Airflow</u>	9,4 m³/h
<u>Airflow with L.N.A.</u>	8,3 m³/h
Acoustical noise	14,9 dB(A)
Acoustical noise with L.N.A.	12,2 dB(A)
Static pressure	2,26 mm H ₂ O
Static pressure with L.N.A.	1,75 mm H ₂ O
Input power (typical)	0,46 W
Input power (max.)	0,6 W
Input current (typical)	0,04 A
Max. input current	0,05 A
Operating voltage	12 V
<u>Voltage PWM signal</u>	5 V
MTTF	> 150.000 h
Scope of delivery	• Low-Noise Adaptor (L.N.A.) • 4-pin y-cable • 30cm extension cable • OmniJoin™ adaptor set • NA-AV3 anti-vibration mounts • Fan screws
<u>Warranty</u>	6 years

